

# Product Information Sheet



**Product:** HLA1113DBBL

## 1. General Information

**Type of Product** : Laminar Flow HEPA Filter  
**Filter Frame** : Extruded Aluminium  
**Spacer** : Hotmelt  
**Bonding** : 2 Component Polyurethane  
**Gasket** : Frothed Polyurethane  
**Grid** : Double Grid  
**Flange** : No Flange

## 2. Technical Information Filter Media

**Type of Filter Media** : 100% high efficiency micro glass fiber paper  
**Media Structure / Bonding** : Borosilicate glass microfibers with an acrylic resin binder  
**Base Weight** : 78 g/m<sup>2</sup>  
**Thickness** : 0.42 mm  
**Flammability (acc. DIN 53438)** : n.a.

## 3. Technical Specification Filter

**Product** : HLA1113DBBL  
**Dimensions (BxHxD)** : 305x305x150 [mm]  
**Surface Area** : 2,8 [m<sup>2</sup>]  
**Volume Air Flow** : 150 [m<sup>3</sup>/h]  
**Air Velocity** : 0,45 [m/s]  
**Media Velocity** : 0,01 [m/s]  
**Efficiency at MPPS** : ≥ 99,95 [%]  
**Initial Pressure Drop** : 120 [Pa]  
**Final Pressure Drop** : 500 [Pa]  
**Filter Classification** : H13 acc. EN1822  
**Maximum Temperature** : 70 [°C]  
**Maximum rel. Humidity** : 90 [%]

All data are average indicative values with usual manufacturing and testing tolerances. We reserve the right to modify performance data without prior notice. Specific performance data will require our written confirmation.

Date of revision:

7-11-2017

rev.: 2 revised by OK

page 1 of 1

### AFPRO Filters B.V.

Berenkoog 67, 1822 BN Alkmaar / P.O. Box 482, 1800 AL Alkmaar

Tel.: +31 (0) 72-567 55 00, Fax.: +31 (0) 72-561 51 94

[www.afprofilters.com](http://www.afprofilters.com)