

Product Information Sheet



Product: HLA1113DBEL

1. General Information

Type of Product : Laminar Flow HEPA Filter
Filter Frame : Extruded Aluminium
Spacer : Hotmelt
Bonding : 2 Component Polyurethane
Gasket : Frothed Polyurethane
Grid : Double Grid
Flange : No Flange

2. Technical Information Filter Media

Type of Filter Media : 100% high efficiency micro glass fiber paper
Media Structure / Bonding : Borosilicate glass microfibers with an acrylic resin binder
Base Weight : 78 g/m²
Thickness : 0.42 mm
Flammability (acc. DIN 53438) : n.a.

3. Technical Specification Filter

Product : HLA1113DBEL
Dimensions (BxHxD) : 305x610x150 [mm]
Surface Area : 5,5 [m²]
Volume Air Flow : 300 [m³/h]
Air Velocity : 0,45 [m/s]
Media Velocity : 0,02 [m/s]
Efficiency at MPPS : ≥ 99,95 [%]
Initial Pressure Drop : 120 [Pa]
Final Pressure Drop : 500 [Pa]
Filter Classification : H13 acc. EN1822
Maximum Temperature : 70 [°C]
Maximum rel. Humidity : 90 [%]

All data are average indicative values with usual manufacturing and testing tolerances. We reserve the right to modify performance data without prior notice. Specific performance data will require our written confirmation.

Date of revision:

7-11-2017

rev.: 1 revised by OK

page 1 of 1

AFPRO Filters B.V.

Berenkoog 67, 1822 BN Alkmaar / P.O. Box 482, 1800 AL Alkmaar

Tel.: +31 (0) 72-567 55 00, Fax.: +31 (0) 72-561 51 94

www.afprofilters.com